

图号/DWG NO.
57HT84-D0821-002





Diagram of a 4-wire motor terminal box. The top left terminal is labeled "RED A+" and "A+". The bottom left terminal is labeled "BLUE A-" and "A-". The bottom right terminal is labeled "B+ GREEN" and "B+". The bottom right terminal is labeled "B- BLACK" and "B-". A motor symbol "M" is shown in the center.

励磁顺序(2相励磁)VS. 旋转方向
EXCITING SEQUENCE(TWO PHESES)
VS. DIRECTION OF ROTATION


步 距 角/STEP ANGLE	1.8° ±5%
相 数/NO. OF PHASES	2
额定电压/RATED VOLTAGE	3.2V
额定电流/RATED CURRENT	4.0A
电 阻/RESISTANCE	0.8ohm±10% AT25℃
电 感/INDUCTANCE	3.7mH±20% AT 1kHz, 1Vrms
保持力矩/HOLDING TORQUE	2.6N. m
运行力矩/(AT —PPS) RUNNING TORQUE(AT —PPS)	——以上/MIN (——V. DC, ——A/相(PHASE), ——相励磁/EX)
绝缘耐压/DIELECTRIC STRENGTH	500V A. C 1分钟/MINUTE
绝缘电阻/INSULATION RESISTANCE	100MΩ 以上/MIN.
绝缘等级/INSULATION CLASS	CLASS B
温度上升/TEMPERATURE RISE	80K MAX.
转子惯量/ROTOR INERTIA	520g. cm ²
重 量/WEIGHT	约/APPROX. 克/g
允许轴向负载/ALLOWABLE THRUST LOAD	5N
允许径向负载/ALLOWABLE RADIAL LOAD	25N(轴端/ON THE SHAFT END)
运行环境温度/OPERATION AMBIENT TEMP.	-20℃——+50℃
运行环境湿度/OPERATION AMBIENT HUM.	15%——90%
寿 命/LIFE	5000小时/HOURS

	STEP	A+	B+	A-	B-	
CW ↓	1	+	+	-	-	↑ CCW
	2	-	+	+	-	
	3	-	-	+	+	
	4	+	-	-	+	

从安装面看为顺时针方向
CLOCKWISE VIEW FROM MOUTING SIDE

1. 额定电流, 两相同时通电/AT RATED CURRENT, TWO PHASES ON.
2. 热阻法: 电机安装在84*84*T5的铝板上, 电机线圈两端通额定电压, 0PPS /MEASURED BY RESISTANCE METHOD. MOUNT WITH ALUMINUM HEAT SINK 84*84*T5 AT TWO WINDING BE EXCITED BY RATED VOLTAGE, 0PPS, 2PHASE ON.
3. 寿命测试条件: 整步, 运行速度为500PPS, 轴承的表面温度不超过70° C LIFE TEST CONDITION: 2PHASE EXCITING, FULL STEP, AT 500PPS. STARTING PULSE, BEARING TEMPERATURE SHOULD BE 70° C MAX.

已受控

CONFIRMED&ACCEPTED BY CUTOMER (客户确认&接受)										
		COMPANY CHOP&SIGNATURE (盖章&签名)								
一般公差 TOLERANCE		±0.3/±3°	版本 REV.	年 月 日 DATE	变更番号 ECR NO.	变 更 内 容 REVISIONS	设计 BY	备注 NOTE	REV.	A
设计/DESIGNED				比例 SCALE		型 号/MODEL 57AM26-4A	三维图 THIRD ANGLE PROJECTION 			
				单位 UNIT	mm					
审核/CHECKED				深圳锐特机电技术有限公司						