




图号/DWG NO.	86HSM155-K1440-009
------------	--------------------



接线图/WIRING DIAGRAM



电机特性参数/ELECTRICAL PARAMETER

步 距 角/STEP ANGLE	1.8° ±5%
相 数/NO. OF PHASES	2
额定电压/RATED VOLTAGE	4.32V
额定电流/RATED CURRENT	6.0A
电 阻/RESISTANCE	0.72ohm±10% AT25℃
电 感/INDUCTANCE	8.3mH±20% AT 1kHz, 1Vrms
保持力矩/HOLDING TORQUE	12N. m
运行力矩/(AT —PPS) RUNNING TORQUE(AT —PPS)	——以上/MIN (——V. DC, ——A/相(PHASE), ——相励磁/EX)
绝缘耐压/DIELECTRIC STRENGTH	500V A.C 1分钟/MINUTE
绝缘电阻/INSULATION RESISTANCE	100MΩ 以上/MIN.
绝缘等级/INSULATION CLASS	CLASS B
温度上升/TEMPERATURE RISE	80K MAX.
转子惯量/ROTOR INERTIA	4000g. cm ²
重 量/WEIGHT	约/APPROX. 5320克/g
允许轴向负载/ALLOWABLE THRUST LOAD	10N
允许径向负载/ALLOWABLE RADIAL LOAD	100N(轴端/ON THE SHAFT END)
运行环境温度/OPERATION AMBIENT TEMP.	-20℃——+50℃
运行环境湿度/OPERATION AMBIENT HUM.	15%——90%

备注/NOTE):

1. 额定电流, 两相同时通电/AT RATED CURRENT, TWO PHASES ON.
2. 热阻法: 电机安装在84*84*75的铝板上, 电机线圈两端通额定电压, OPSS
/MEASURED BY RESISTANCE METHOD. MOUNT WITH ALUMINUM HEAT SINK 84*84*75
AT TWO WINDING BE EXCITED BY RATED VOLTAGE, OPSS, 2PHASE ON.
3. 寿命测试条件: 整步, 运行速度为500PPS, 轴承的表面温度不超过70° C
LIFE TEST CONDITION: 2PHASE EXCITING, FULL STEP, AT 500PPS. STARTING PULSE,
BEARING TEMPERATURE SHOULD BE 70° C MAX.

1000线光电编码器出线定义


定义	Z+	Z-	EB+	EB-	EA+	EA-	5V	GN
线色	灰	黑	绿	黄	棕	白	红	蓝

励磁顺序(2相励磁)VS. 旋转方向
EXCITING SEQUENCE(TWO PHESES)
VS. DIRECTION OF ROTATION

STEP	A+	B+	A-	B-
1	+	+	-	-
2	-	+	+	-
3	-	-	+	+
4	+	-	-	+

从安装面看为顺时针方向
CLOCKWISE VIEW FROM MOUNTING SIDE

已受控

CONFIRMED&ACCEPTED BY CUSTOMER (客户确认&接受)									
COMPANY CHOP&SIGNATURE (盖章&签名)									
一般公差 TOLERANCE ±0.3/±3°		版本 REV.	年 月 日 DATE	变更番号 ECR NO.	变 更 内 容 REVISIONS		设计 BY	备注 NOTE	REV. A
设计/DESIGNED		比例 SCALE			型 号/MODEL 86A12ECZ-3M			三视图 THIRD ANGL PROJECTION	
									
审核/CHECKED		单位 UNIT		mm	深圳锐特机电技术有限公司			页 SHEET	1/1