


接线图:Wiring Diagram




励磁顺序vs.旋转方向  
Exciting Sequence vs. Direction of Rotation

STEP	A+	B+	A-	B-	
1	+	+	-	-	CCW ↑
2	-	+	+	-	
3	-	-	+	+	
4	+	-	-	+	

CW ↓

从安装面看为顺时针方向  
Clockwise view from mouting side

标签 Label Detail



规格 Specifications

1.相数 Number of Phase	2
2.步距角 Step Angle	1.8 °
3.额定电压 Rated Voltage	3.15V
4.额定电流 Rated Current	5.0 A
5.保持力矩 Holding Torque	3.0 N.m Typ. ( Two phase on/rated current )
6.相电阻 Phase Resistance	0.63ohm±10% ( 20°C )
7.相电感 Phase Resistance	2.2 mH±20% ( 1kHz 1V rms )
8.转子惯量 Rotor Inertia	0.84kg.cm <sup>2</sup>
9.电机重量 Motor Weight	1.42KG
10.绝缘等级 Insulation Class	B ( 130°C )

		单位:毫米 Unit:mm		批准 Approve		锐特技术 ShenZhen Rtelligent Technology Co.LTD 深圳锐特机电技术有限公司		Hybrid Stepping Motor	
		第一视角画法 First angle method		标准化 Standard		型号: D57AM30 V3.0			
		未注线性与角度尺寸公差均按 GB/T 1804-M		工艺 Technology		图号:			
		未注形状与位置尺寸公差均按 GB/T 1184-K		审核 Check		图号:			
原始版本 Original revision				设计 Design		图号:			
REV.	版本记录 REVISION RECORD	DATE	UNLESS OTHERWISE SPECIFIED	NAMES	SIGNATURE	DATE	TYPE:	Rev.A	SCALE 1:1 Sheet 1 of 1