



规格 Specifications

1.相数 Number of Phase	2
2.步距角 Step Angle	1.8°
3.额定电压 Rated Voltage	24V
4.额定电流 Rated Current	5.0 A
5.保持力矩 Holding Torque	2.2 N.m Typ.(Two phase on/rated current)
6.相电阻 Phase Resistance	0.35ohm±10%(20 °C)
7.相电感 Phase Resistance	2.1 mH±20%(1kHz 1V rms)
8.转子惯量 Rotor Inertia	0.480kg.cm^2
9.电机重量 Motor Weight	1.25KG
10.绝缘等级 Insulation Class	B(130 °C)

F			单位:毫米 Unit:mm	批准 Approve			<div>Hybrid Stepping Motor</div> <div>ShenZhen Rtelligent Technology Co.LTD</div> <div>深圳锐特机电技术有限公司</div>					
			第一视角画法 First angle method	标准化 Standard								
			未注线性与角度尺寸公差均按 GB/T 1804-M	工艺 Technology								
			未注形状与位置尺寸公差均按 GB/T 1184-K	审核 Check			型号:	ITD57AM21-D0821-24V-M				F
				设计 Design			图号:	ITD57AM21-D0821-24V-M				
		原始版本 Original revision										
	REV.	版本记录 REVISIONRECORD	DATE	UNLESSOTHERWISESPECIFIED	NAMES	SIGNATURE	DATE	TYPE:		Rev.A	SCALE 1:1	Sheet 1 of 1